



Birchwood Laboratories LLC
7900 Fuller Road
Eden Prairie, MN 55344
Tel: 952 937 7931
Fax: 952 937 7979
www.birchwoodtechnologies.com

DRI-TOUCH® AMBER Low-VOC Rust Preventive
Operating Instructions

DESCRIPTION

DRI-TOUCH® AMBER Low-VOC Rust Preventive is a high grade, water-displacing corrosion inhibitor for all metal surfaces. It can be applied to wet or dry surfaces and forms a thin, transparent protective film that penetrates recessed areas and dries to a non-dimensional, semi-solid film that will not drain off the parts or wick off into packaging materials. Contains no silicone or wax. Harmless to plastics, synthetic rubbers and paints. Complies with California Rule 1144, as promulgated by the South Coast Air Quality Management District.

APPLICATION

Apply at Room Temperature to wet or dry parts by dipping, brushing or conventional low pressure spray equipment. Allow 1-2 minute contact time to penetrate recesses and displace water; then allow parts to drain and dry for 30-60 minutes. Drying may be accelerated with warm air flow.

PHYSICAL PROPERTIES

Appearance	Pale, amber liquid
Film Thickness	0.1-.2 mil – transparent film
Flash Point, TCC	248° F
Coverage per gallon	1500 square feet per gallon
VOC Content	0.2 pounds per gallon maximum

PROTECTIVE PROPERTIES

Salt Spray Test (ASTM B-117)	96 hours minimum.
Humidity Test (ASTM D-1748)	800 hours minimum.
Water Displacement (MIL-C-16173E)	Meets Class II, Grade 3
Stain Test (MIL-C-2235A)	Pass

REMOVAL

Solvent wash or heated alkaline detergent cleaners.

PACKAGING

1, 5 gallon pails and 55 gallon non-returnable drums. Keep container closed during storage to prevent solvent loss.

Before Using This Product – Please Read, Understand and Follow all the Precautions shown on the Product Label and on the Safety Data Sheet.

The Safety Data Sheet can be found on our website: www.birchwoodtechnologies.com

Use Appropriate Warning Labels on any Container used to Store or Apply this Product.

NOTE: The information contained herein is provided in good faith and is believed to be correct as of the date below. However, Birchwood Laboratories LLC makes no representation as to the comprehensiveness or accuracy of the information. It is expected that individuals receiving the information will exercise their independent judgment in determining its appropriateness for a particular purpose. Accordingly, Birchwood Laboratories LLC will not be responsible for damages of any kind resulting from the use of or reliance upon such information.

DRI-TOUCH® AMBER Low VOC
© Birchwood Laboratories LLC
07/2015

(Product Numbers 811750, 811751, 811758)